

VOLTEC VTD-500SH



VOLTEC VTD-500SH representa la perfección en elegancia y discreción en cámaras de vigilancia. Es una familia de dispositivos que permiten facilidad de instalación y adaptación a cualquier tipo de superficie. Son productos confeccionados bajo un estricto y riguroso control de calidad. Cada unidad es inspeccionada de manera individual antes de ser despachada para reducir al máximo el retorno de unidades defectuosas. Nuestras cámaras son fabricadas con los mejores polímeros brindándole un producto de excelente acabado y un material de alta resistencia.



Especificaciones:

- High Sensitivity 0.1Lux@F=1.2
- 500 TV lines resolution
- S/N ratio more than 48dB
- Auto white balance/AGC/BLC
- Power source: DC12V

VOLTEC VTD-500SH



Model	DOM-AA510-B1	DOM-AA520-B1
Video Output Format	NTSC	PAL
Type	Dome	
Pick-up Device	Sharp 1/3" Color Hi-Res. CCD	
Picture Element	768 (H) X 494 (V)	752 (H) X 582 (V)
Resolution	500 TV lines	
Synchronous System	Internal	
Scanning System	525 lines / 60 fields	625 lines / 50 fields
Signal / Noise Ratio	More than 48 dB (AGC off)	
Gamma Correction	0.45	
Lens Options (mm)	f 2.5 / f 3.6 (STD) / f 4.3 / f 6.0 / f 8.0; F2.0	
Minimum Illumination	0.1 LUX @ F=1.2	
Video Output	1.0 Vp-p / 75Ω[, BNC or F-Connector	
Vertical Frequency	60Hz	50Hz
Current Consumption	110mA	
Operating Temperature	-10°C ~ + 50°C	
Auto Electronic Shutter	1/60 ~ 1/100,000 sec.	1/50 ~ 1/110,000 sec.
Power Source	DC 12V	
Dimension (mm)	100(Ø) X 60 (H)	
Weight	125g	